

METAPACE

Metapace L-22D - Compact desktop label printer

www.metapace.com

Highlights

- Compact direct thermal label printer in a complete package
- Versatile with different media
- Print speed: 152 mm/sec.
- Supports all common printer languages
- Includes label design software

Technical specifications

Print

Printing method	Direct thermal
Print width	max. 56.9 mm
Print length	6 – 2000 mm
Print speed	max. 152 mm/sec.
Resolution	8 dots/mm (203 dpi) / 12 dots/mm (300 dpi) (optional)

Media

Media type	Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width	15 – 60 mm
Roll diameter	max. 130 mm
Core diameter	12.5 – 38.1 mm
Media strength	0.06 – 0.2 mm

Electronics

Memory	Flash: 128 MB, RAM: 64 MB DDR3
Interfaces	USB 2.0, Serial, Ethernet (option), WiFi (option)
Power supply	AC 100V – 240V, DC 24V, 2,5A
Barcodes	All Standard 1D and 2D Barcodes
Reliability	MCBF: min. 12 months; Auto-Cutter: min. 6 months; TPH: min. 6 months

Software

Emulation	EPL, EPL II, ZPL, ZPL II, SLCS
Drivers	Windows 2000, XP (32/64 Bit), 2003 Server (32/64 Bit), Vista (32/64 Bit), Windows 7 (32/64 Bit), Linux (ab 2.4.8), Mac OS (ab 10.4)
Labeldesigner	Metapace Label Designer Software

Specifics

Options	Auto-Cutter, Dispenser, Ethernet, WiFi
---------	--

Warranty

Period	24 months
Dimension (WxHxD)	120 x 230 x 170 mm
Weight	1.36 kg



Drivers
by Seagull™

L-22D

METAPACE