

Thermal Portable Printer RPP-02

RPP-02

Portable Printer RPP-02 With Battery;
2" Thermal printer;
Easy paper loading;
Small size.



Specifications

- **Printing way:** Thermal sensitive line dot method
- **Paper width:** 56mm
- **Paper thickness:** 60 ~ 80 μ m
- **Valid printing width:** 48 mm
- **Resolution:** 8 dot/mm (230 dpi)
- **Dot /line:** 384 dots
- **Printing speed:** 50-80 mm/s
- **Printing content:** Support any language
- **Outer dimension:** 102*108*50mm
- **Weight:** 340g
- **Rolling paper Diameter:** \leq 30.5mm
- **Interface:** Original IR(RAW_IR), VIR, IrDA (IrCOMM) RS232 port, blue tooth, interfaces varied with different models.
- **Environment parameters:** Working temperature: -10 $^{\circ}$ C~ 50 $^{\circ}$ C
Working humidity: 20% ~ 85%
Storing temperature : -20 $^{\circ}$ C~ 70 $^{\circ}$ C
Storing humidity: 5% ~ 95%
- **Paper feeding method:** Easy paper loading
- **Mark position:** detecting mark position
- **Paper sensor:** LED indicator flashes when come to paper end meanwhile alarm.
- **Printing Command:** ESC/POS compatible with commands set
- **Power:** 1600 mAh rechargeable li-ion battery
- **Power alarm:** indicator flashes when printer will run out of power and give out two short hoots. When running out of power, buzzle will give out interval warning to indicate charging.