

LCD 150



4:3
DISPLAY


CAPACITIF
MULTI-TOUCH


AFFICHEUR*
CLIENT INTÉGRÉ


LECTEUR*
DALLAS


BADGE*


IP65

CONFIGURATIONS



LCD150

LCD 150

LCD	15" LED
Luminosité	300 nits
Résolution	1024 x 768
Touch Screen	PCAP Touch
Angle de vision	0° ~ 90°

ENTRÉES / SORTIES

USB	1x USB2.0 (Type A) 1x USB2.0 (Type B to PC)
VGA	1x DB15
Button on/off	2 (Power, Auto) + LED

ALIMENTATION

Alimentation	36W / 12V
DC Jack	1x 2 pin

OPTIONS

MSR	3-Track MSR (USB)
iButton	iButton (USB)
Afficheur client	LCM display 2 x 20 caractères (USB)

CERTIFICAT

EMC & Sécurité	FCC Class A, CE Mark, LVD
----------------	---------------------------

ENVIRONNEMENT

Température en fonctionnement	0°C ~ 40°C (32°F ~ 104°F)
Température de stockage	-20°C ~ 60°C (-4°F ~ 140°F)
Humidité	20% ~ 85% RH sans condensation

DIMENSIONS



360 x 218 x 250 à 339 mm

POIDS

4,34 kg

VESA

VESA Mount 100 x 100



Document non contractuel, susceptible de modifications sans préavis. OXHOO © 2019

